

## NOTES:

- 1. CONSTRUCTION SHALL CONFORM TO THESE REQUIREMENTS EXCEPT AS OTHERWISE DIRECTED BY THE COUNTY ENGINEER.
- 2.R1=ANCHOR BOLT DIAMETER DIMENSION. RADIUS AND BOLT PATTERN TO SUIT POLE BASE USED.
- 3.IN AREAS WHERE CONCRETE SIDEWALKS WILL BE POURED AFTER THE POLE FOUNDATION IS INSTALLED, POUR FOUNDATION TO BOTTOM ELEVATION OF SIDEWALK. IN AREAS WITHOUT CONCRETE AROUND FOOTING, CONSTRUCT A 2' X 2' CONCRETE PAD (4" THICK).
- 4.FOUNDATION BOLTS SHALL NOT BE CUT OFF FOR ANY REASON. EXTENSION COUPLERS SHALL NOT BE PERMITTED.
- 5.LEVELING OF BASE SHALL CONFORM TO THE REQUIREMENTS OF STANDARD DRAWING NO. 620.

## COUNTY OF SONOMA DEPARTMENT OF TRANSPORTATION AND PUBLIC WORKS

## BASE DETAIL STANDARD STREET LIGHT POLE

DATE: MAY 2004 REVISED:  APPROVED BY: SCALE: DRAWING NO		NONE	618	
DATE: MAY 2004 REVISED:	APPROVED BY:		DRAWING	NO.
	DATE: MAY 2004	REVISE	ED:	